

## Portable Recovery Pak™ (RP)

### GENERAL DESCRIPTION

YORK® Portable Recovery Pak™ system offers all the features a field service technician needs. These compact, portable, self-contained units are easy to operate for fast chiller evacuation. Capacities are AHRI certified to assure performance as specified. These units are self-contained packages specifically engineered to provide refrigerant recovery capabilities for commercial and industrial applications requiring serviceability. It consists of a refrigerant compressor (high pressure), oil separator & heater, water-cooled condenser, filter, gauges, refrigerant valves and hoses to remove, replace and distill CFC and HCFC refrigerants. All necessary controls and safety devices are permanently mounted. The RP package is made portable via wheels & swivel casters with lock brakes.



RP-2200

### TECHNICAL DATA

- (2) Eight foot Refrigerant Hoses with valves
- Permanent Ball Valves for Refrigerant Serviceability
- Relief Valves
- Wheels Included
- Standard 1-year parts warranty coverage.

### RP-2200 UNIT FEATURES & BENEFITS

- AHRI Certified Performance
- “Lawnmower” Style configuration

### RP-4400 UNIT FEATURES & BENEFITS

- AHRI Certified Performance
- **Industry Performance Leader!**
- Solid heavy-duty construction and components



RP-4400

MODEL	HIGH PRESSURE	
	RP-2200	RP-4400
REFRIGERANT	CFC-12 HCFC-22 CFC-500 HFC-134a	
PUSH/PULL LIQUID RECOVERY (LB/MIN)	140.00	483.91
VAPOR REFRIGERANT RECOVERY (LB/MIN)	2.86	15.08
HIGH TEMP VAPOR RECOVERY (LB/MIN)	1.28	19.84
SHUT OFF VACUUM (inHg vac)	> 17.2	22.46
WORKING PRESSURE	100 - 300 LBS	100 - 300 LBS
MOTOR SIZE	1-1/2 HP	10 HP
*STANDARD VOLTAGES	115/1/60 208/1/60 230/1/60	460/3/60
PLUGS INCLUDED	Yes	4 Prong
WEIGHT	150 lb.	850 lb.
LxWxH	24" X 24" X 28"	57" X 32" X 65"
WHEELS INCLUDED	Yes	Yes
RELIEF VALVES	Yes	Yes
ASME APPROVED	N/A	N/A
AHRI CERTIFIED & STAMPED	Yes	Yes

R-22 Refrigerant ratings displayed.

\*Alternate power configurations available.

